



Large Diameter

Petroduct smoothwall HDPE conduit is ideal for installation of cable or fiber in any underground application. Corrosion & chemical resistant, HDPE is lightweight but exceptionally durable for demanding site applications.

Features

- Made from Prime HDPE Pipe Grade Resin
- Smooth inner wall
- Specified printline/markings every two feet Manufactured to ASTM D2447, D3035(F2160), D1693, D3350 and NEMA TC7 Specifications
- RUS listed
- Large diameter is stocked in 50' lengths.
- Joint pipe only 8" & larger.
- Custom lengths available upon request.
- Standard Color is black (striping available)
- Additional specifications and colors available upon request (minimum order quantities will apply).



STANDARD SPECIFICATIONS LARGE DIAMETER

SIZE	PRODUCT PART #	NOMINAL O.D.	MIN I.D.	MEAN WALL	WEIGHT LBS/ FT
8.00"	P800SDR7	8.6250	6.0130	1.3060	12.35850
	P800SDR9	8.6250	6.5930	1.0155	9.9880
	P800SDR11	8.6250	6.9630	0.830	8.3590
	P800SDR13.5	8.6250	7.2710	0.6775	6.9390
	P800SDR15.5	8.6250	7.4450	0.5730	6.1000
	P800SDR17	8.6250	7.5490	0.5375	5.5970
	P800SDR21	8.6250	7.7540	0.4355	4.5910
	P800SDR26	8.6250	7.9220	0.3520	3.7440
	P800SDR32.5	8.6250	8.0620	0.2810	3.0120
SIZE	PRODUCT PART #	NOMINAL O.D.	MIN I.D.	MEAN WALL	WEIGHT LBS/ FT
10.00"	P1000SDR7	10.7500	7.4900	1.6300	19.2340
	P1000SDR9	10.7500	8.2200	1.2650	15.5244
	P100SDR11	10.7500	8.6780	1.0355	12.9830
	P1000SDR13.5	10.7500	9.0620	0.8440	10.7740
	P1000SDR15.5	10.7500	9.2800	0.7350	9.4900
	P1000SDR17	10.7500	9.4090	0.6705	8.6950
	P1000SDR21	10.7500	8.6600	0.5450	7.1961
	P1000SDR26	10.7500	9.8700	0.4400	5.8695
	P1000SDR32.5	10.7500	10.0500	0.3500	4.7097
SIZE	PRODUCT PART #	NOMINAL O.D.	MIN I.D.	MEAN WALL	WEIGHT LBS/ FT
12.00"	P1200SDR7	12.7500	8.8890	1.9305	27.0250
	P1200SDR9	12.7500	9.7470	1.5015	21.8528
	P120SDR11	12.7500	10.2930	1.2285	18.3135
	P1200SDR13.5	12.7500	10.7480	1.0010	15.2168
	P1200SDR15.5	12.7500	11.0060	0.8720	13.4013
	P1200SDR17	12.7500	11.1600	0.7950	12.2972
	P1200SDR21	12.7500	11.4630	0.6435	10.0799
	P1200SDR26	12.7500	11.7100	0.5200	8.2284
	P1200SDR32.5	12.7500	11.9180	0.4160	6.6387