

## Outside Plant Conduit

### Petroduct™/HDPE/Smooth/Ribbed



For specialized installation of underground cable Petroduct™ Ribbed provides superior friction reduction and flexibility. Manufactured from quality HDPE resin, Petroduct™ Ribbed offers maximum strength and adaptability on long pulls with numerous turns and elevation changes.

#### Features:

- \* Made from Prime HDPE Pipe Grade Resin
- \* Ribbed inner wall
- \* Available with pre-installed tape or empty
- \* Available pre-lubricated with Petroflex's own ProPull™ Lube
- \* Sequential footage markings every two feet
- \* Packaged on lightweight steel reels or in coils
- \* Manufactured to ASTM D2447, D3035, D3485, D2239, F2160 and NEMA TC7 Specifications

<u>Size</u>	<u>Part #</u>	<u>Min. I.D.</u>	<u>Nom. O.D.</u>	<u>Mean Wall</u>	<u>Weight lbs./ft</u>
1.00"	PR100SDR13.5	1.101	1.315	0.107	0.1727
	PR100SDR11	1.055	1.315	0.130	0.2048
	PR100SCH40	0.979	1.315	0.143	0.2223
1.25"	PR125SDR13.5	1.340	1.660	0.135	0.2708
	PR125SDR11	1.258	1.660	0.161	0.3203
	PR125SCH40	1.310	1.660	0.150	0.3098
1.50"	PR150SDR13.5	1.518	1.900	0.151	0.4217
	PR150SDR11	1.444	1.900	0.183	0.4145
	PR150SCH40	1.520	1.900	0.155	0.3800
2.00"	PR200SDR13.5	1.921	2.375	0.186	0.5368
	PR200SDR11	1.831	2.375	0.229	0.6458
	PR200SCH40	1.967	2.375	0.164	0.4792

\*R prefix to any part # indicates cut-to-length & does not change fit, form or function (i.e. RPR100SDR13.5, RPR150SDR13.5)

\* 2, 3, or 4 colors available paralleled onto one reel as a special order(see reel chart)

\* Standard colors(striping is available):

