



Corrugated Petroduct™

For specialized installation of cable, PetroDuct™ Corrugated Duct provides superior friction reduction and flexibility. Manufactured from quality High Density Polyethylene, PetroDuct™ Corrugated Duct offers maximum flexibility in tight turns combined with light weight and superior economy. PetroDuct™ Corrugated affords maximum pulling ease and lubrication effectiveness when installed with ProPull™ Lube.



Features

- Corrugated Wall
- Packaged on light weight steel reels or coils. Coils may be shrink wrapped and palletized.
- Pre-installed with 1100# PullTape™
- Available in standard colors: Black (UV), Orange or Red

*R prefix to any part # indicates cut-to-length & does not change fit, form or function (i.e. RPC100, RPC125, RPC150, RPC200)

* Not designed for direct bury

STANDARD SPECIFICATIONS CORRUGATED PETRODUCT™

SIZE	PRODUCT PART #	NOMINAL O.D.	MIN I.D.	MEAN WALL	WEIGHT LBS/FT	MEAN DENSITY
1.00"	PC100	1.31	1.00	0.040	0.0765	0.950
1.25"	PC125	1.54	1.25	0.040	0.1030	0.950
1.50"	PC150	1.90	1.57	0.040	0.1251	0.950
2.00"	PC200	2.37	2.04	0.040	0.1754	0.950